

DY-602C

Woofer:	6.5" carbon fiber Cone
Tweeter:	1" ALuminum DOME
Impedance:	4Ω
Sensitivity:	89dB
Frequency Response:	65Hz - 20kHz
Rated Power:	80 Watts
Cutout Diameter:	/



DY-603C

Woofer:	6.5"PMI kevlar Cone
Tweeter:	1" ALuminum DOME
Impedance:	4Ω
Sensitivity:	89dB
Frequency Response:	65Hz - 20kHz
Rated Power:	100 Watts
Cutout Diameter:	/



DY-692

Woofer:	6*9" carbon fiber Cone
Tweeter:	1" ALuminum DOME
Impedance:	4Ω
Sensitivity:	89dB
Frequency Response:	60Hz - 20kHz
Rated Power:	60 Watts
Cutout Diameter:	/



DY-652

Woofer:	6.5" carbon fiber Cone
Tweeter:	1" ALuminum DOME
Impedance:	4Ω
Sensitivity:	88dB
Frequency Response:	65Hz - 20kHz
Rated Power:	50 Watts
Cutout Diameter:	/

Car Speaker
Dyatt Audio Co., Ltd



DY-602

Woofer:	6" carbon fiber Cone
Tweeter:	1" ALuminum DOME
Impedance:	4Ω
Sensitivity:	88dB
Frequency Response:	65Hz - 20kHz
Rated Power:	40 Watts
Cutout Diameter:	/



DY-52

Woofer:	5.25" carbon fiber Cone
Tweeter:	1" ALuminum DOME
Impedance:	4Ω
Sensitivity:	87dB
Frequency Response:	70Hz - 20kHz
Rated Power:	30 Watts
Cutout Diameter:	/



DY-572

Woofer:	5*7" carbon fiber Cone
Tweeter:	1" ALuminum DOME
Impedance:	4Ω
Sensitivity:	88dB
Frequency Response:	75Hz - 20kHz
Rated Power:	30 Watts
Cutout Diameter:	/



DY-462

Woofer:	4*6" carbon fiber Cone
Tweeter:	3/4" ALuminum DOME
Impedance:	4Ω
Sensitivity:	87dB
Frequency Response:	75Hz - 20kHz
Rated Power:	60 Watts
Cutout Diameter:	/



DY-42

Woofer:	4" carbon fiber Cone
Tweeter:	3/4" ALuminum DOME
Impedance:	4Ω
Sensitivity:	86dB
Frequency Response:	75Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/

Dyatt Audio Co., Ltd

Marine Speaker



DY-C625

Woofer:	6.5"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	87dB
Frequency Response:	90Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



DY-C825

Woofer:	8"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	88dB
Frequency Response:	80Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



DY-C6925

Woofer:	6*9"Injection Cone
Tweeter:	1" ALuminum DOME
Impedance:	8Ω
Sensitivity:	88dB
Frequency Response:	70Hz - 20kHz
Rated Power:	25 Watts
Cutout Diameter:	/



DY-YT625A

Woofer:	6.5"Injection Cone
Tweeter:	1.5" Ti DOME
Impedance:	8Ω
Sensitivity:	88dB
Frequency Response:	70Hz - 20kHz
Rated Power:	80 Watts
Cutout Diameter:	/



DY-YT625A

Woofer:	8"Injection Cone
Tweeter:	1.5" Ti DOME
Impedance:	8Ω
Sensitivity:	90dB
Frequency Response:	60Hz - 20kHz
Rated Power:	100 Watts
Cutout Diameter:	/



DY-H1224

Woofer:	12"fiber Glass Cone
Tweeter:	/
Impedance:	4Ω
Sensitivity:	87dB
Frequency Response:	35Hz - 250kHz
Rated Power:	1500 Watts
Cutout Diameter:	/



DY-H12E

Woofer:	12"fiber Glass Cone
Tweeter:	/
Impedance:	4Ω
Sensitivity:	87dB
Frequency Response:	35Hz - 250kHz
Rated Power:	1500 Watts
Cutout Diameter:	/



DY-H1524

Woofer:	15"fiber Glass Cone
Tweeter:	/
Impedance:	4Ω
Sensitivity:	88dB
Frequency Response:	35Hz - 250kHz
Rated Power:	1800 Watts
Cutout Diameter:	/



SW-12B

Woofer:	12"Paper Cone
Tweeter:	/
Impedance:	4Ω
Sensitivity:	88dB
Frequency Response:	25Hz - 150kHz
Rated Power:	500 Watts
Cutout Diameter:	/



SW-12A

Woofer:	12"Paper Cone
Tweeter:	/
Impedance:	4Ω
Sensitivity:	88dB
Frequency Response:	25Hz - 150kHz
Rated Power:	500 Watts
Cutout Diameter:	/

HUIZHOU DEYUE ELECTRONIC PRODUCTS CO., LTD

www.dyattaudio.com